



PRODUCT
INFORMATION

Tack Coat

Asphalt Emulsion Binder

COMPOSITION

Tack Coat is a slow setting anionic emulsion specifically designed for priming old pavements before patching and overlays.

PHYSICAL DATA

Tack Coat promotes adhesion between existing pavements and new asphaltic concrete. Tack Coat is a non-polluting, environmentally friendly, solvent-free material that retards water intrusion and reduces shoving caused by rolling.

APPLICATION

Sweep or blow area removing all vegetation, dirt and debris. Do not apply to a wet surface. Apply straight from container with a broom, brush, roller or spray equipment. Thin overlays should have an 8" wide band around perimeter of patch, and .1 gal/sq. yd. in the center. Failed areas which have been excavated should have vertical faces coated. Cut 1 to 1 with water.

YIELD

Variable due to temperature and pavement conditions. Material when applied is brown. Do not apply asphaltic concrete until Tack Coat has turned black.

CLEAN-UP

Tools may be cleaned with water before material dries. Dried material can be removed with an approved solvent. For hands and skin, use a waterless hand cleaner.

AVAILABILITY

Tack Coat is available in 5 gallon pails, 55 gallon drums and bulk quantities.

CAUTIONS

Contains asphaltic materials. Harmful or fatal if swallowed. Do not induce vomiting. Avoid prolonged contact with skin and breathing of vapors. Flush skin with water immediately. Use with adequate ventilation. In case of contact with eyes, flush eyes with water and call physician.
KEEP FROM FREEZING.



Bringing Integrity to the Surface.

Kansas City, MO Denver, CO
Oklahoma City, OK Ramsey, MN
Tulsa, OK Ft. Worth, TX

Manufactured By Vance Brothers Kansas City, Missouri 800.821.8549 www.vancebrothers.com