



Bringing Integrity to the Surface.®

MATERIAL SAFETY DATA SHEET

5201 Brighton, P.O. Box 300107

Kansas City, MO 64130

Phone: 816-923-4325/ 800-821-8549 FAX: 816-923-6472

Emergency Phone Number (CHEMTREC): 800-424-9300

HMIS HAZARD RATING	
1	HEALTH
0	FIRE
0	REACTIVITY

I. PRODUCT INFORMATION

TRADE NAME EBL, CPEM-1, PMCRS-1S, RoadTac	C.A.S. NUMBER Mixture
SYNONYMS Novachip Tack, Cationic Tack	PRODUCT CODE NUMBER

II. PHYSICAL DATA

BOILING POINT @ 760 MM Hg 212°F	% VOLATILES BY VOLUME 30-40%	SOLUBILITY IN H2O BY WEIGHT % Miscible
SPECIFIC GRAVITY 1.0 ± 0.2 @ 60°F	MELTING POINT Not Applicable	EVAPORATION RATE (BUTYL ACETATE = 1) Slower
VAPOR DENSITY (AIR = 1) > 1.0	VAPOR PRESSURE Not Determined	APPEARANCE AND ODOR Brown to Black Material--Sweet Odor

III. HAZARDOUS COMPONENTS

C.A.S. NUMBER	MATERIAL OR COMPONENT	%	HAZARD DATA
8052-42-4	[1] Asphalt	60 - 70	TLV/TWA - 5mg/m ³ for asphalt fumes TLV/STEL - 10 mg/m ³ for asphalt fumes
7732-18-5	[2] Water	30 - 40	Not applicable
106107-54-4	[3] Proprietary Polymer	0 - 5	Not applicable

IV. HEALTH HAZARD INFORMATION

EXPOSURE LIMITS	TLV/TWA 5 mg/m³ for oil mist	TLV/STEL 5 mg/m³ for oil mist	TLV/PEL Not Established	ODOR THRESHOLD LIMIT Not Applicable
-----------------	---	--	-----------------------------------	---

ROUTES OF EXPOSURE AND EFFECTS AS REQUIRED BY 29CFR1910.1200

INHALATION	Vapors that are released during the curing process are not known to contain hazardous materials. However, effects from raw materials include irritation to the eye, nose, and respiratory tracts of test animals. Health effects are not to be expected if proper personal safety and hygiene is observed.
INGESTION	High viscosity oils, i.e. asphalt, have been shown to be less toxic when ingested than lower viscosity, higher volatility oils. Product contains acidic material (0.4%) and could cause burns in the mouth, esophagus, and stomach.
SKIN ABSORPTION	Skin absorption could occur through normal skin contact and/or through wounds exposed to asphalt products. Product contains less than 0.4% acidic material. Effects could include irritation and possible tissue damage or dermatitis. Health effects are not be expected if proper personal safety and hygiene is observed.
SKIN CONTACT	Product contains less than 0.4% acidic material. Direct contact may cause irritation and/or itching. Pre-existing skin disorders may be aggravated by exposure to this product. Severe effects could include tissue burns, irritation and dermatitis.
EYE CONTACT	Documentation indicates that contact lenses should not be worn when exposed to this product. This product contains less than 0.4% acidic material and can cause inflammation, irritation, and possible corneal burns.
ACUTE OVEREXPOSURE	Skin effects may include irritation and itching. Product contains less than 0.4% acidic material and may cause tissue burns or dermatitis. Any pre-existing skin conditions may be aggravated by exposure to this product.
CHRONIC OVEREXPOSURE	Chronic health effects are not expected if proper personal safety and hygiene is observed. Pre-existing skin disorders may be aggravated by repeated or prolonged exposure to this product.

V. EMERGENCY AND FIRST AID PROCEDURES

INHALATION	Vapors that are released during the curing process are not known to contain hazardous materials. However, if breathing is difficult, move person to fresh air and seek prompt medical attention.
INGESTION	DO NOT induce vomiting. In general, emesis induction is unnecessary for high viscosity, low volatility oils such as asphalt and grease. Avoid all digestible oils, fats, and alcohol which may increase intestinal absorption. Seek medical attention.
SKIN CONTACT	Flush area with water to cool. Wash affected area with waterless hand cleaner, followed by water and a mild detergent. DO NOT use solvents! For relief from irritation, apply hand lotion. If irritation persists, seek medical attention.
EYE CONTACT	Flush eyes with water for 15 minutes while holding eyelids open. If subject is wearing contact lenses, immediately seek an ophthalmologist for treatment.

VI. SPECIAL PROTECTION INFORMATION

<p>VENTILATION</p>	<p>Care must be taken to assure that the TLV/TWA of 5mg/m³ for oil mist is not exceeded. Normal exterior application should not require the need for mechanical ventilation. Application must be made downwind from operator.</p>	<p>PERSONAL PROTECTIVE EQUIPMENT</p>
<p>RESPIRATORY PROTECTION</p>	<p>If needed, use an approved OSHA/NIOSH particulate and organic vapor canister respirator, or a positive atmosphere supplied air respirator as described in 29 CFR 1910.134.</p>	<p>DUST/ORGANIC VAPOR RESPIRATOR</p>
<p>EYE PROTECTION</p>	<p>Goggles and full-face shield are recommended when handling this material.</p>	<p>GOGGLES FULL-FACE SHIELD</p>
<p>SKIN PROTECTION</p>	<p>Flannel-lined Neoprene or Nitrile gloves are recommended.</p>	<p>CHEMICAL RESISTANT GLOVES</p>
<p>OTHER PPE</p>	<p>Rubber or leather footwear is recommended. All clothing saturated with this product should be discarded.</p>	<p>BOOTS</p>

VII. FIRE AND EXPLOSION DATA

<p>FLASH POINT Not Applicable</p>	<p>AUTOIGNITION TEMPERATURE Not Applicable</p>	<p>LOWER FLAMMABLE LIMIT Unknown</p>
<p>EXTINGUISHING MEDIA This product contains water and will not burn until all moisture has been removed. If fire should occur, extinguish with foam, carbon dioxide or dry chemical extinguishers.</p>		
<p>SPECIAL FIRE FIGHTING PROCEDURES Fire fighters should wear full protective equipment and self-contained breathing apparatus.</p>		
<p>UNUSUAL FIRE AND EXPLOSION HAZARDS Water sprayed on burning product may cause frothing, steam, and eruptions.</p>		

VIII. REACTIVITY DATA

<p>CONDITIONS CONTRIBUTING TO INSTABILITY Since this is a water-based emulsion, settling will occur. The settling rate is dependent on the dilution and storage temperature. NOTE: Care should be taken to prevent this material from freezing.</p>
<p>INCOMPATIBILITY This material is incompatible with bases. DO NOT heat above 212°F. All additives should be evaluated before use in the field.</p>
<p>HAZARDOUS DECOMPOSITION PRODUCTS Irritating or toxic vapors may be released when this material is burned.</p>
<p>CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION None known.</p>

IX. SPILL AND LEAK PROCEDURES

SPILL CONTROL PROCEDURE

If possible, stop source of leak. Dike and contain to eliminate environmental contamination. For small spills, squeegee into thin layer and cover with dirt or aggregate. If material enters a waterway, notify police, local EPA and the National Response Center (1-800-424-8802)

NEUTRALIZING CHEMICALS

DO NOT use water. This material is highly miscible and water will increase the volume of the spill. If appropriate, pump material into holding vessel and bind with sand or lime dust.

WASTE DISPOSAL

If disposal is necessary, contact your state environmental agency for guidance with disposal methods and waste receiving locations in your area.

X. SPECIAL PRECAUTIONS

ENVIRONMENTAL

- 1. This product is considered an oil under EPA-CWA Section 311. Spills into water sources must be reported to 1-800-424-8802.**
- 2. If this product becomes a waste material, refer to 40 CFR 261.21 (RCRA) for latest waste disposal regulations and waste stream number.**
- 3. This product is listed in the EPA/TSCA inventory (40 CFR 700 to end).**

LABELING

- 1. "KEEP FROM FREEZING" labels are recommended.**
- 2. This material is not regulated by the Department of Transportation.**

XI. REFERENCES

- | | |
|--|---|
| <ol style="list-style-type: none"> 1. BITUMEN SAFETY CODE (ISBN-085501-319-2) 2. CAUSTIC SODA HANDBOOK, VULCAN CHEMICAL 3. CLINICAL TOXICOLOGY OF COMMERCIAL PRODUCTS, 5TH EDITION 4. DOCUMENTATION OF THRESHOLD LIMIT VALUES, 4TH EDITION 5. ENCYCLOPEDIA OF SURFACTANTS, VOLUME III 6. EPA/CWA SECTION 311 | <ol style="list-style-type: none"> 7. HYGIENE AND SANITATION, VOLUME 33 8. NFPA 325M, 704 9. POISONING, TOXICOLOGY, SYMPTOMS, TREATMENTS 10. 29 CFR, 40 CFR AS NOTED WITHIN 11. REGISTRY OF TOXIC EFFECTS OF CHEMICAL SUBSTANCES |
|--|---|

NOTE: This material safety data sheet is intended as a source of information for persons involved in any and all phases of handling this material, from production to final application, as required by 29 CFR 1910.1200. The health data provided is based on the nature of the raw constituents. This material is a mixture and the health effects as such have not been evaluated.

XII. ENVIRONMENTAL INFORMATION

1. THIS PRODUCT CONTAINS THE FOLLOWING EXTREMELY HAZARDOUS SUBSTANCE(S)

(SECTION 302 AND 304):	<u>COMPONENT</u>	<u>TPQ(LBS)</u>	<u>RQ(BLS)</u>
	N/A	N/A	N/A

2. THIS PRODUCT CONTAINS THE FOLLOWING CERCLA HAZARDOUS SUBSTANCE(S)

(SECTION 302 AND 304):	<u>COMPONENT</u>	<u>RQ(LBS)</u>	<u>WEIGHT %</u>
	N/A	N/A	N/A

3. THIS PRODUCT HAS THE FOLLOWING HAZARDS (SECTION 311 AND 312):

	<u>YES</u>	<u>NO</u>
IMMEDIATE	X	X
DELAYED	X	X
FIRE	X	X
PRESSURE	X	X
REACTIVITY	X	X

4. THIS PRODUCT CONTAINS THE FOLLOWING TOXIC CHEMICALS

(SECTION 313):	<u>COMPONENT</u>	<u>CAS#</u>	<u>WEIGHT %</u>
	N/A	N/A	N/A

CARCINOGENITY:	<u>NTP</u>	<u>IARC MONOGRAPHS</u>	<u>OSHA</u>
	NO	NO	NO

The information provided in this material safety data sheet has been obtained and compiled from sources believed to be reliable. This information relates to the specific material designated and may not be valid for such material used in combination with any other material or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. Vance Brothers, Inc. does not accept liability for any loss or damage that may occur from the use of this information nor do we offer warranty against patent.

VANCE BROTHERS, INC.

5201 BRIGHTON, KANSAS CITY, MO 64130 (816) 923-4325
 380 W 62nd AVE, DENVER, CO 80216 (303) 341-2604
 4908 N BRYANT, OKLAHOMA CITY, OK 73121 (405) 427-1389
 9306 E. 11TH, SUITE A, TULSA, OK 74112 (918) 838-2533
 14021 AZURITE ST NW, RAMSEY, MN 55303 (612) 421-4034
 2201 BRENNAN AVE, BLDG B, FT. WORTH, TX (817) 624-0000

DATE

August 4, 2009

PREPARED BY

Stan Fronckewicz