

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture
Product Name: Ultra Blend
Product Code: 706, 707, 708
Synonyms: Coal Tar & Asphalt Driveway Sealer

1.2. Intended Use of the Product

Use of the substance/mixture: Construction

1.3. Name, Address, and Telephone of the Responsible Party

Company

Vance Brothers
 5201 Brighton Ave., P.O. Box 300107
 Kansas City, MO 64130
 T 816-923-4325/ 800-821-8549 - F 816-923-6472

1.4. Emergency Telephone Number

Emergency Number : 800-424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Classification (GHS-US)

Skin Sens. 1	H317
Muta. 1B	H340
Carc. 1A	H350
Repr. 1B	H360
Aquatic Chronic 4	H413

Full text of H-phrases: see section 16

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H317 - May cause an allergic skin reaction.
 H340 - May cause genetic defects.
 H350 - May cause cancer.
 H360 - May damage fertility or the unborn child.
 H413 - May cause long lasting harmful effects to aquatic life.

Precautionary Statements (GHS-US)

: P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P261 - Avoid breathing vapors, mist, and spray.
 P272 - Contaminated work clothing must not be allowed out of the workplace.
 P273 - Avoid release to the environment.
 P280 - Wear eye protection, protective clothing, and protective gloves.
 P302+P352 - IF ON SKIN: Wash with plenty of water.
 P308+P313 - If exposed or concerned: Get medical advice/attention.
 P321 - Specific treatment (see Section 4 on this SDS).
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
 P362+P364 - Take off contaminated clothing and wash it before reuse.
 P405 - Store locked up.
 P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. Risk of thermal burns on contact with molten product. Molten material may produce fumes that are toxic or irritating.

Ultra Blend

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	%	Classification (GHS-US)
Water	(CAS No) 7732-18-5	50 - 64	Not classified
Pitch, coal tar, high-temperature	(CAS No) 65996-93-2	16 - 26	Comb. Dust Skin Sens. 1, H317 Muta. 1B, H340 Carc. 1A, H350 Repr. 1B, H360 Aquatic Chronic 4, H413
Proprietary Clay	Proprietary*	10 - 20	Not classified
Asphalt	(CAS No) 8052-42-4	4 - 6	Carc. 2, H351

*The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200].

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice.

First-aid Measures After Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

First-aid Measures After Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash contaminated clothing before reuse. In molten form: Cool skin rapidly with cold water after contact with molten product, Removal of solidified molten material from skin requires medical assistance.

First-aid Measures After Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention. In molten form: Protect skin and eyes from contact with molten material.

First-aid Measures After Ingestion: Rinse mouth. Do NOT induce vomiting. Seek medical attention immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/Injuries: May cause an allergic skin reaction. There are potential chronic health effects to consider.

Symptoms/Injuries After Inhalation: May cause respiratory irritation.

Symptoms/Injuries After Skin Contact: May cause skin irritation.

Symptoms/Injuries After Eye Contact: May cause eye irritation.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: May cause cancer. May damage fertility or the unborn child. May cause genetic defects.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂).

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Do not allow run-off from fire fighting to enter drains or water sources. Do not breathe fumes or vapors from fire. Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Other Information: Refer to Section 9 for flammability properties.

Ultra Blend

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all contact with skin, eyes, or clothing. Avoid breathing vapor, mist, or spray. Handle in accordance with good industrial hygiene and safety practice.

6.1.1. For Non-emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Evacuate unnecessary personnel.

6.1.2. For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection. Use appropriate personal protection equipment (PPE).

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material, then place in suitable container. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Precautions for Safe Handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapors, mist, spray.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Wash hands and forearms thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use.

Incompatible Products: Strong acids. Strong bases. Strong oxidizers.

Storage Area: Store locked up.

7.3. Specific End Use(s) Construction

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), or OSHA (PEL).

Ultra Blend		
USA ACGIH	ACGIH TWA (mg/m ³)	0.1 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	0.2 mg/m ³
Pitch, coal tar, high-temperature (65996-93-2)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.2 mg/m ³
USA ACGIH	ACGIH chemical category	Confirmed Human Carcinogen
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	0.1 mg/m ³ (Cyclohexane-extractable fraction)
USA IDLH	US IDLH (mg/m ³)	80 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	0.2 mg/m ³ (benzene soluble fraction)
Asphalt (8052-42-4)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.5 mg/m ³ (fume, inhalable fraction)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen fume, coal tar-free
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	5 mg/m ³ (fume)
Proprietary Clay		
USA ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust)

Ultra Blend

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

		5 mg/m ³ (respirable dust)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)

8.2. Exposure Controls

Appropriate Engineering Controls

: Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment

: Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing

: Chemically resistant materials and fabrics.

Hand Protection

: Wear chemically resistant protective gloves.

Eye Protection

: Chemical safety goggles.

Skin and Body Protection

: Wear suitable protective clothing.

Respiratory Protection

: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

Thermal Hazard Protection

: If material is hot, wear thermally resistant protective gloves.

Environmental Exposure Controls

: Do not allow the product to be released into the environment.

Consumer Exposure Controls

: Do not eat, drink or smoke during use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Gray to Black Material
Odor	: Mothball Odor
Odor Threshold	: No data available
pH	: No data available
Evaporation Rate	: Slower
Melting Point	: Not applicable
Freezing Point	: No data available
Boiling Point	: 100 °C (212 °F)
Flash Point	: No data available
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor Pressure	: 25 mm Hg (at 70 °F/21.1 °C)
Relative Vapor Density at 20 °C	: > 1.0
Relative Density	: No data available
Specific Gravity	: 1 (+/- 0.2 at 60 °F/15.56 °C)
Solubility	: Water: Miscible
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available

9.2. Other Information

VOC content : 50 - 64

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity: Hazardous reactions will not occur under normal conditions.

10.2. Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Ultra Blend

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- 10.4. Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Do not freeze.
- 10.5. Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers.
- 10.6. Hazardous Decomposition Products:** Thermal decomposition generates: Carbon oxides (CO, CO₂). Irritating or toxic vapors.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information On Toxicological Effects

Acute Toxicity: Not classified

Pitch, coal tar, high-temperature (65996-93-2)	
LD50 Oral Rat	> 15000 mg/kg
LD50 Dermal Rat	> 2000 mg/kg
Asphalt (8052-42-4)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
Proprietary Clay	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 5000 mg/kg

Skin Corrosion/Irritation: Not classified

Serious Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: May cause genetic defects.

Carcinogenicity: May cause cancer.

Pitch, coal tar, high-temperature (65996-93-2)	
IARC group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Asphalt (8052-42-4)	
IARC group	2B
National Toxicology Program (NTP) Status	Twelfth Report - Items under consideration.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

Reproductive Toxicity: May damage fertility or the unborn child.

Specific Target Organ Toxicity (Single Exposure): Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May cause respiratory irritation.

Symptoms/Injuries After Skin Contact: May cause skin irritation.

Symptoms/Injuries After Eye Contact: May cause eye irritation.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: May cause cancer. May damage fertility or the unborn child. May cause genetic defects.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General : This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

Ecology - Water : May cause long lasting harmful effects to aquatic life

12.2. Persistence and Degradability

Ultra Blend	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

Ultra Blend	
Bioaccumulative Potential	Not established.
Pitch, coal tar, high-temperature (65996-93-2)	
BCF fish 1	< 0.13
Log Pow	6.04

Ultra Blend

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Asphalt (8052-42-4)	
BCF fish 1	(no bioaccumulation expected)
Log Pow	> 6

12.4. Mobility in Soil No additional information available

12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Sewage Disposal Recommendations: Do not empty into drains. Do not dispose of waste into sewer.

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

SECTION 14: TRANSPORT INFORMATION

14.1. In Accordance with DOT Not regulated for transport

14.2. In Accordance with IMDG Not regulated for transport

14.3. In Accordance with IATA Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1 US Federal Regulations

Ultra Blend	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
Pitch, coal tar, high-temperature (65996-93-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Water (7732-18-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Asphalt (8052-42-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Proprietary Clay	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2 US State Regulations

Pitch, coal tar, high-temperature (65996-93-2)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances	
U.S. - Pennsylvania - RTK (Right to Know) List	
Asphalt (8052-42-4)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	
Proprietary Clay	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 06/16/2015

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Aquatic Chronic 4	Hazardous to the aquatic environment - Chronic Hazard Category 4
Carc. 1A	Carcinogenicity Category 1A
Carc. 2	Carcinogenicity Category 2
Comb. Dust	May form combustible dust concentrations in air

Ultra Blend

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Muta. 1B	Germ cell mutagenicity Category 1B
Repr. 1B	Reproductive toxicity Category 1B
Skin Sens. 1	Skin sensitization Category 1
H317	May cause an allergic skin reaction
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H360	May damage fertility or the unborn child
H413	May cause long lasting harmful effects to aquatic life

NFPA Health Hazard


: 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA Fire Hazard

: 1 - Must be preheated before ignition can occur.

NFPA Reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)