



PRODUCT
INFORMATION

Gator Seal

COMPOSITION

Gator Seal is a heavy bodied asphalt binder fortified with mineral filler, fibers and silica sand.

PHYSICAL DATA

Gator Seal is a cold applied material that is used to seal alligatored areas in asphalt pavements. Gator Seal is supplied in ready to use form although more silica sand may be added if desired. A small amount of water may be added as well for workability. Severely alligatored areas should be removed and replaced. Dries to a flat black color.

APPLICATION

Squeegee a thin coat over the entire area. Apply coat(s) of pavement sealer over application of dried Gator Seal for best results. In all applications, allow to dry overnight before submission to vehicular traffic.

YIELD

One gallon will seal approximately 20-50 square feet, depending on porosity of surface.

DRYING TIME

Gator Seal will dry to the touch in one hour under good weather conditions. Allow to dry overnight before allowing traffic. Be sure to check the treated surface before opening to traffic.

CLEAN-UP

Rinse tools with water soon after using. Dried material can be removed with an approved solvent. For hands and skin, use a waterless handcleaner.

AVAILABILITY

Gator Seal is available in 5 gallon pails.

CAUTIONS

Do not allow material to freeze. Apply only when temperatures are above 50 degrees F. and when it is not expected to freeze that night. Do not apply if rain is imminent or if freezing temperatures are expected within 24 hours.



Bringing Integrity to the Surface.

Kansas City, MO Denver, CO
Oklahoma City, OK Ramsey, MN
Tulsa, OK Ft. Worth, TX