

# ADVANTAGE *Sport Coating Systems*™

## ADVANTAGE PRIME

### DESCRIPTION

ADVANTAGE Prime is a clear acrylic latex primer designed to improve the bonding characteristics of concrete or asphalt surfaces.

### USES

ADVANTAGE Prime is used as a prime coat prior to the application of ADVANTAGE Acrylic Fill to concrete tennis courts, playgrounds and recreational surfaces. It is also used when bonding problems exist on asphalt surfaces as well.

### SURFACE PREPARATION

New concrete surfaces should cure 45 days prior to any coating application. **(When installing over concrete surfaces, the concrete should be installed with a suitable vapor barrier and without concrete curing compound.)** For best results, the concrete should be thoroughly cleaned with compressed air and then etched with a commercial grade of 85% phosphoric acid. Mix 1 gallon phosphoric acid per ten gallons of water. Solution should be spread with a nylon or polypropylene bristle broom. Once etching is complete, concrete must be thoroughly flooded. Treated surfaces must be squeegeed dry. Do not allow rinse water to sit.

New asphalt pavements should cure a minimum of 14-21 days prior to any coating applications. Asphalt surfaces should be cleaned with compressed air and free from oil, grease, dirt and other foreign matter. Embedded dirt should be brushed thoroughly prior to any coating application. Grease and oil spots should be primed with an approved oil spot primer. See ADVANTAGE Specifications for complete information.

### MIX DESIGN

Use ADVANTAGE Prime as is - do not dilute.

When ordering ADVANTAGE Prime, figure 20 square yards per gallon.

### APPLICATION

Apply ADVANTAGE Prime to properly prepared surface by brush, roller or spray.

### CLEAN-UP

Rinse tools with water soon after using. Dried material can be removed with an approved solvent.

### SHELF LIFE

Approximately 12 months

### PHYSICAL PROPERTIES

Weight/Gallon	8.44 lbs. per gallon
Drying Time	Touch: 1 hour
Application Temperature	50° F. and rising

### PRECAUTIONS

Keep from freezing. Harmful if swallowed. Read material safety data sheets.

### SHIPPING WEIGHT

53 gallon drum	491 lbs.
5 gallon pail	44 lbs.

Warranty: This product is guaranteed with respect to uniformity and quality. Since its use is beyond the control of the manufacturer, liability for damage shall in no case exceed the purchase price on the quantity of material used. Warranty is void on multi-coat applications if material made by other manufacturers is used with this product.



Manufactured By:

**Vance Bros Inc**

Kansas City, Missouri 800-821-8549

[www.vancebrothers.com](http://www.vancebrothers.com)

*Kansas City, MO Denver, CO*  
*Oklahoma City, OK Ramsey, MN*  
*Tulsa, OK Albuquerque, NM*

