

Advantage Patch Binder

Description

Advantage Patch Binder is a high-strength acrylic bonding liquid designed for mixing with Portland cement and silica sand to patch depressions in asphalt and concrete surfaces. Advantage Patch Binder enables patches to set rapidly up to 3/4" in thickness. Deeper depressions may require additional applications.

Uses

Advantage Patch Binder is used to patch depressions in asphalt and concrete tennis courts, playgrounds and recreational surfaces.

Surface Preparation

New asphalt pavements should cure a minimum of 14-21 days prior to any coating application. New concrete surfaces should cure 28 days prior to any coating application. **(When installing over concrete surfaces, the concrete must be installed with a suitable vapor barrier and without concrete curing compounds.)** Surfaces should be thoroughly cleaned with compressed air and free from oil, grease, dirt and other foreign matter. Embedded dirt should be brushed thoroughly prior to any coating application. Grease and oil spots should be primed with an approved oil spot primer. Concrete surfaces should be acid etched with a commercial grade of 85% phosphoric acid. See Advantage Specifications for complete information.

Mix Design

3 gallons Advantage Patch Binder
100 lbs. Silica Sand (40 - 70 mesh)
2 gallons fine Portland cement (Mix Patch Binder and sand to desired thickness. Then add fine Portland cement and mix thoroughly. Do not add water to mix.)

Application

Apply with a trowel, squeegee or straight edge. Be sure to "feather the edges" to make a level surface. Deeper depressions may require additional applications.

Clean-up

Rinse tools with water soon after using. Dried material can be removed with an approved solvent.

Shelf Life

Approximately 12 months

Physical Properties

Weight/Gallon ... 8.8 lbs. per gallon

Drying Time ... Touch: 1 hour

Application Temperature ... 50° F and rising

Precautions

Keep from freezing. Harmful if swallowed. Read material safety data sheets.

Shipping Weight

55 gallon drum ... 528 lbs.

30 gallon drum ... 276 lbs.

5 gallon pail ... 46 lbs.

Warranty: This product is guaranteed with respect to uniformity and quality. Since its use is beyond the control of the manufacturer, liability for damage shall in no case exceed the purchase price on the quantity of material used. Warranty is void on multi-coat applications if material made by other manufacturers is used with this product.

phone: 800.821.8549

816.923.4325

fax: 816.923.6472

web: chooseadvantage.com

► 5201 Brighton

Kansas City, Missouri 64130

Manufactured by Vance Bros Inc